

SUBSTITUTE SPECIFICATION 1

A METHOD OF RECORDING AUDIOVISUAL CONTENT IN A
COMMUNICATIONS NETWORK



RELATED APPLICATIONS

This is a U.S. National Phase Application under 35
USC 371 of International Application PCT/FR2004/003388
filed on 24 December 2004.

FIELD OF THE INVENTION

10 The present invention relates to a method of
recording audiovisual content in a communications
network.

One particularly advantageous application of the
invention is the field of remote recording audiovisual
15 content.

BACKGROUND OF THE INVENTION

There are prior art methods for the remote recording
of audiovisual content broadcast on broadcast channels of
20 a communications network that consist in requesting a
broadcast channel to broadcast a content selected by the
user to a personal digital recorder (PDR) situated in the
user's home, for example.

By way of example, users can find it necessary to
25 use this kind of remote recording method if they are far
from home and realize that they have forgotten to program
a recording on a PDR while they were at home.

Using an office computer, mobile telephone, or
personal digital assistant (PDA), a user can then program
30 recording remotely by sending a request to the broadcast
channel concerned.

However, although they meet this type of need well,
the above prior art remote recording methods do not solve
other problems associated with recording audiovisual
35 content, in particular if the broadcast channel whose
content the user would like to record cannot be received,
for example because that channel is not part of the

package to which the user subscribes or because the user's receiver can receive only one channel at a time and is being used by another person on another broadcast channel at the time the content that the user wishes to
 5 record is broadcast.

Thus the technical problem to be solved by the present invention is that of proposing a method of recording audiovisual content in a communications network that would enable users to record audiovisual content
 10 that they are unable to record directly on their own receivers, either because the content cannot be received thereby, or because a receiver is not designed to receive more than one broadcast channel at a time.

15 **SUMMARY OF THE INVENTION**

In accordance with the present invention, the solution to the stated technical problem consists in a method of recording audiovisual content in a communications network including at least one network
 20 recorder able to record audiovisual content broadcast on a plurality of broadcast channels, characterized in that said audiovisual content is recorded by a network recorder at the request of a user having a communications terminal able to exchange information with at least one
 25 network recorder via said communications network, said method comprising the following steps:

- the network recorder declaring itself in the network, the declaration indicating at least:
 - * a means of access to said recorder,
 - 30 * a list of broadcast channels whose broadcast audiovisual content can be recorded by the network recorder,
- the user using a terminal to select a network recorder able to record at least one required audiovisual
 35 content and to connect thereto using said access means in order to request the recording of said at least one audiovisual content, said request including an

identification of said at least one audiovisual content to be recorded that consists in a unique reference of said content and/or an identification of an instance of said content consisting of at least the identification of the broadcast channel of said instance accompanied by the indication of a broadcast time band, and

5 · the network recorder sending a response to the user's recording request containing, if the request is accepted, an identification of the accepted recording request for each content to be recorded.

Accordingly, from a PDR, a personal computer, a mobile telephone, or a personal assistant, a user can at any time request the network recorder to record an audiovisual content on any broadcast channel, even those channels to which the user does not have direct access, in order afterwards to transfer the recorded audiovisual content to the receiver of the user's choice (PDR, PC, PDA) and to watch it at a time when the receiver is available.

20 One aspect of the invention is a method of declaring an audiovisual content network recorder in a communications network including at least one network recorder able to record audiovisual content broadcast on a plurality of broadcast channels, characterized in that said method comprises at least the step of declaring the network recorder in the network, the declaration indicating at least:

 * a means of access to said recorder,
 * a list of broadcast channels whose broadcast audiovisual content can be recorded by the network recorder.

Another aspect of the invention is a method of discovering and submitting requests to an audiovisual content recorder in a communications network including at least one network recorder able to record audiovisual content broadcast on a plurality of broadcast channels, characterized in that said audiovisual content is

recorded by a network recorder at the request of a user having a communications terminal able to exchange information with at least one network recorder via said communications network, said method comprising the
5 following steps:

- using the terminal to select a network recorder able to record at least a required audiovisual content and connecting thereto using a means of access to said recorder in order to request the recording of said at
10 least one audiovisual content, said request including an identification of said at least one audiovisual content to be recorded that consists in a unique reference of said content and/or an identification of an instance of said content consisting of at least the identification of
15 the broadcast channel of said instance accompanied by the indication of a broadcast time band, and

- receiving a response to the user's recording request sent by the recorder and containing, if the request is accepted, an identification of the accepted
20 recording request for each content to be recorded.

According to the invention, said time band indication includes the broadcast start time and either the broadcast end time or the duration of the broadcast on the broadcast channel of said instance.

25 The invention further consists in a method of recording audiovisual content in a communications network. The recording method comprises the following steps:

- connecting to said terminal a network recorder
30 able to record at least one required audiovisual content selected by said terminal using a means of access to said recorder to request the recording of said at least one audiovisual content, said request including an identification of said at least one audiovisual content
35 to be recorded that consists in a unique reference of said content and/or an identification of an instance of said content consisting of at least the identification of

the broadcast channel of said instance accompanied by the indication of a broadcast time band, and

- sending a response to the user's recording request containing, if the request is accepted, an identification of the accepted recording request for each content to be recorded.

When it has received a recording request, the network recorder sends a response to the user who sent the request.

- 10 If the request is accepted, the invention envisages a number of options in addition to identification of the accepted request, namely: the response from the network recorder contains said unique reference of the requested audiovisual content, the response from the network
15 recorder contains the programmed end of recording time and/or the cost of said recording, or the response from the network recorder contains the time for which the network recorder will keep the recording.

- 20 The discovery and request submission method of the invention also offers the user the option to review and revise a request, by said method further including the steps of the user formulating a request to cancel a recording request that has been accepted or to delete a content that has been recorded by the network recorder,
25 that request specifying at least the identification of the recording request that has been accepted.

- 30 To enable the user to determine at any time the stage reached by the network recorder in processing a request, the discovery and request submission method and the recording method of the invention also include the steps of:

- if the request is accepted, the network recorder receiving from the terminal a recording request status request indicating at least said identification of the
35 accepted recording request, and
- the network recorder sending a response to the recording request status request containing at least the

identification of the accepted recording request and the status of the request.

Said recording request status request preferably contains said unique reference of the content and/or the identification of the user.

The response of the recorder to the recording request status request may take various forms, depending on the situation:

- in the case of a request that has not yet been executed, the response to the recording request status request contains the unique reference of the content and/or the programmed end date and time,
- in the event of an unknown request, the response to the recording request status request contains the unique reference of the content,
- in the event of failure of the request, the response to the recording request status request contains the unique reference of the content,
- if the content is available, the response to the recording request status request contains an address at which the recorded content is available. In which case, the response contains the unique reference of the content and/or the time for which the network recorder will keep the recording.

One aspect of the invention is a device for declaring a network recorder of audiovisual content in a communications network including at least one network recorder able to record audiovisual content broadcast on a plurality of broadcast channels, characterized in that said declaration device comprises at least:

- means for generating a declaration indicating at least:
 - a means of access to said recorder,
 - a list of broadcast channels whose broadcast audiovisual content can be recorded by the network recorder, and

· means for sending said declaration of the network recorder into the network.

One aspect of the invention is a device for recording audiovisual content in a communications network including at least one network recorder able to record audiovisual content broadcast on a plurality of broadcast channels, characterized in that said audiovisual content is recorded by a network recorder at the request of a user having a communications terminal able to exchange information with at least one network recorder via said communications network, said recording device including:

· means for connecting to said terminal a network recorder able to record at least one required audiovisual content selected by said terminal using a means of access to said recorder in order to request the recording of said at least one audiovisual content, said request including an identification of said at least one audiovisual content to be recorded that consists in a unique reference of said content and/or an identification of an instance of said content consisting of at least the identification of the broadcast channel of said instance accompanied by the indication of a broadcast time band, and

· means for sending a response to the user's recording request containing, if the request is accepted, an identification of the accepted recording request for each content to be recorded.

Another aspect of the invention is a network recorder able to record audiovisual content in a communications network including at least one network recorder able to record audiovisual content broadcast on a plurality of broadcast channels, characterized in that said audiovisual content is recorded by a network recorder at the request of a user having a communications terminal able to exchange information with at least one network recorder via said communications network, said network recorder including:

· means for connecting to said terminal a network recorder able to record at least one required audiovisual content selected by said terminal using a means of access to said recorder in order to request the recording of
5 said at least one audiovisual content, said request including an identification of said at least one audiovisual content to be recorded that consists in a unique reference of said content and/or an identification of an instance of said content consisting of at least the
10 identification of the broadcast channel of said instance accompanied by the indication of a broadcast time band, and

· means for sending a response to the user's recording request containing, if the request is accepted,
15 an identification of the accepted recording request for each content to be recorded.

The invention also consists in a device for discovering and submitting requests to a recorder of audiovisual content in a communications network including
20 at least one network recorder able to record audiovisual content broadcast on a plurality of broadcast channels, characterized in that said audiovisual content is recorded by a network recorder at the request of a user having a communications terminal able to exchange
25 information with at least one network recorder via said communications network, said discovery and request submission device including:

· means for choosing by means of the terminal a network recorder able to record at least one required
30 audiovisual content and for connecting thereto using a means of access to said recorder in order to request the recording of said at least one audiovisual content, said request including an identification of said at least one audiovisual content to be recorded that consists in a
35 unique reference of said content and/or an identification of an instance of said content consisting of at least the identification of the broadcast channel of said instance

accompanied by the indication of a broadcast time band,
and

· means for receiving a response to the user's
recording request sent by the recorder containing, if the
5 request is accepted, an identification of the accepted
recording request for each content to be recorded.

One aspect of the invention is a communications
terminal in a communications network including at least
one network recorder able to record audiovisual content
10 broadcast on a plurality of broadcast channels,
characterized in that said audiovisual content is
recorded by a network recorder at the request of a user
having said communications terminal able to exchange
information with at least one network recorder via said
15 communications network, said terminal including:

· means for choosing by means of the terminal a
network recorder able to record at least one required
audiovisual content and for connecting thereto using a
means of access to said recorder in order to request the
20 recording of said at least one audiovisual content, said
request including an identification of said at least one
audiovisual content to be recorded that consists in a
unique reference of said content and/or an identification
of an instance of said content consisting of at least the
25 identification of the broadcast channel of said instance
accompanied by the indication of a broadcast time band,
and

· means for receiving a response to the user's
recording request sent by the recorder containing, if the
30 request is accepted, an identification of the accepted
recording request for each content to be recorded.

BRIEF DESCRIPTION OF THE DRAWINGS

The following description with reference to the
35 appended drawings, which are provided by way of
non-limiting example, explains in what the invention
consists and how it may be reduced to practice.

Figure 1 is a general flowchart of the recording method of the invention.

Figure 2 is a flowchart of the recording method of the invention in the case of a successful recording request.

Figure 3 is a flowchart of the recording method of the invention in the case of a failed recording request.

Figure 4 is a flowchart of the recording method of the invention in the case of a successful recording request with additional time-delay.

Figure 5 is a flowchart of the recording method of the invention in the case of a successful recording request followed by a cancellation request.

Figure 6 is a flowchart of the recording method of the invention in the case of a successful recording request followed by a failure to record.

Figure 7 is a flowchart of the recording method of the invention in the case of an unknown recording request.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Figure 1 is a general flowchart of a method of recording audiovisual (AV) content in a communications network.

That method involves at least one network recorder, corresponding to the right-hand portion of Figure 1, able to record audiovisual content broadcast on broadcast channels. Network recorder operators offer a user the service of recording on their behalf audiovisual content that they are unable to record themselves, for example because this is not possible as the user does not have an appropriate subscription or does not have access to the broadcast channel that is broadcasting the required AV content or because their receiver is already being used by another person on another broadcast channel. Network recorders can be provided by operators specializing in

this type of service or by the broadcast channels (television channels) themselves.

The network recorder records an audiovisual content at the request of a user, corresponding to the left-hand
5 portion of Figure 1, provided with a terminal able to exchange information concerning recording requests with network recorders via a communications network.

Initially, the network recorders must declare themselves on the communications network, either directly
10 through a recorder website or indirectly via a directory, for example a UDDI (Universal Description Discovery and Integration) directory associated with the SOAP (Simple Object Access Protocol) exchange technology. In which case, the directory has to create a particular "Network
15 Recorders" heading and list in the directory under that heading the network recorders that have been declared.

The declaration of the existence each network recorder in the network (*<TV_Record_Service_Declaration>* data structure) indicates:

20 · preferably, an address of the network recorder (*<RecordServiceAddress>* element), which is the address to which the recording request must be sent, and is either the address of a website or the address of a directory heading,

25 · preferably, a list of the broadcast channels that it can record (*<DeliveryServiceList>* element), able to contain for each channel:

 * preferably, the address of the broadcast channel ("*serviceURL*" attribute), for example as defined
30 by the TV Anytime forum,

 * optionally, the charging policy of the recorder for that broadcast channel (*<ChargingPolicy>* element),

 · optionally, the conversion capabilities of the
35 recorder (*<ConversionCapabilities>* element) consisting of:

* the bit rate reduction capability
(*<BitrateConversionCapability>* element), for example bit
rate reduction from 4 Mbps to 2 Mbps,

* the ability to transcode the audiovisual
5 content (*<TranscodingCapability>* element) into different
audiovisual coding formats, such as MPEG2 to MPEG4
transcoding,

* optionally, the protocols supported for
transferring the recorded AV content to the user's
10 receiver: FTP, streaming, or downloading.

Thus the invention provides two main ways to access
a network recorder. One way to access a network recorder
is to use an address of said recorder in the network.
The other way is to use a directory listing the
15 operations specific to the network recorders, each
network recorder being identified by said operation.

More precisely, according to the invention, said
list of broadcast channels whose broadcast audiovisual
content can be recorded by the network recorder includes
20 the address of each broadcast channel, optionally
accompanied by the charging policy of the network
recorder for each broadcast channel. The broadcast
channel address is a channel identifier codified by a
consortium combining interested companies and
25 organizations, such as the TV Anytime forum.

To enable the user to receive the audiovisual
content recorded by the network recorder subject to
technical conditions compatible with the user's receiver,
the invention provides for the declaration of the network
30 recorder in the network to contain the conversion
capabilities of said recorder, which relate more
particularly to bit rate reduction and/or transcoding of
the audiovisual content.

It should also be pointed out that the bit rate and
35 transcoding constraints in respect of the audiovisual
content emanate from the user, since the invention
teaches that said request should contain the conversion

capabilities required by the user for transferring the recording to the user's terminal.

The user must be in a position to discover the existence of network recorders in order to be able to
 5 select the one able to record the required AV content under the best technical, economic and ergonomic conditions. This can be done:

- either by defining a particular MIME (Multipurpose Internet Mail Extensions) type (e.g. "*application/x-TV-Record-Service-Declaration*"), which, when a file of this
 10 type is received from a website, activates software on the user's receiver for interpreting the *<TV_Record_Service_Declaration>* data structure defined above,
- 15 · or by using a UDDI directory and defining a new "tModel" for AV content recording services enabling any recorder to declare its existence and its capabilities to the directory in the *<TV_Record_Service_Declaration>* data structure defined above.

20 Having selected the best-suited network recorder for recording the required AV content from a website or a directory, the user sends that recorder a recording request (*<TV_Record_Service_Request>* data structure) comprising:

- 25 · preferably, the identification of the user (*<UserId>* attribute) if the user has not been identified some other way, for example at the time of connecting to the recorder (log in and password type connection),
- preferably, an identification of the AV content to
 30 be recorded, which may be:
 - * either a unique reference of said content ("*CRID*" attribute), essentially a simple identification of the content as such,
 - * or the user's own identification of an
 35 instance of that content consisting of:
 - preferably, the identification of the broadcast channel ("*serviceURL*" attribute),

- preferably, the start time ("start" attribute),
- preferably, the end time ("end" attribute) or the duration ("duration" attribute),
- 5 · optionally, the identification of a particular instance ("instanceMetadataId" attribute),
- optionally, the conversion capabilities required by the user.

The network recorder's response to the user's
 10 recording request (<TV_Record_Service_Request_Response> data structure) contains for each content to be recorded an indication:

- either of the success of the recording request (<RecordRequestSuccess> element), this indication
 15 containing:
 - * preferably, the identification of the accepted recording request ("requestId" attribute),
 - * optionally, the identification of the requested content ("CRID" attribute),
 - 20 * optionally, the programmed end of recording time ("recordEndTime" attribute),
 - * optionally, the time to keep the recorded content ("keepDuration" attribute),
 - * optionally, the cost of the recording ("recordCost" and "currency" attributes),
 - 25 · or of the failure of the recording request (<RecordRequestFailure> element), this indication containing:
 - * preferably, the identification of the
 30 requested content ("CRID" attribute),
 - * optionally, the reason for failure of the request ("KOREASON" attribute).

If a recording request from the user fails, the response of the network recorder to the request contains
 35 an identification of content concerned if a plurality of contents was requested. Similarly, the response from the recorder contains the reason for the failure of the

request. A request may fail because the network recorder does not have access to the content requested by the user, for example.

If a recording request is accepted, its status can
5 be requested (<TV_Record_Request_Status_Request> data structure), the request indicating:

- preferably, the identification of the accepted recording request ("requestId" attribute),
- optionally, the identification of the content to
10 be recorded ("CRID" attribute),
- optionally, the identification of the user (<UserId> attribute).

On receiving a request status request, the network recorder sends a response
15 (<TV_Record_Request_Status_Response> data structure) containing:

- in the case of a request that has not yet been executed:
 - * preferably, the identification of the
20 accepted recording request ("requestId" attribute),
 - * preferably, the status of the request ("status" attribute, "runningRequest" value),
 - * optionally, the identification of the content to be recorded ("CRID" attribute),
 - 25 * optionally, the programmed end date and time ("callAfter" attribute),
- in the case of an unknown request (« requestID » attribute not recognized):
 - * preferably, the identification of
30 the accepted recording request ("requestId" attribute),
 - * preferably, the status of the request ("status" attribute, "unknownRequest" value),
 - * optionally, the identification of the content to be recorded ("CRID" attribute),
 - 35 · in the case of a request that fails (for example in the event of an equipment failure):

* preferably, the identification of the
accepted recording request ("requestId" attribute),

* preferably, the status of the request
("status" attribute, "failedRequest" value),

5 * optionally, the identification of the content
to be recorded ("CRID" attribute),

· in the case of a request that has been completed
with the recorded content available:

* preferably, the identification of the
10 accepted recording request ("requestId" attribute),

* preferably, the status of the request
("status" attribute, "contentAvailable" value),

* preferably, the means of recovering the
recorded content ("contentURL" attribute),

15 * optionally, the identification of the content
to be recorded ("CRID" attribute),

* optionally, the time for which the recorder
will keep the recorded content ("keepDuration"
attribute).

20 The user can also request cancellation of a
recording request (<TV_Record_Request_Cancel> data
structure), for example if the user changes his or her
mind, the cancellation request indicating:

* preferably, the identification of the accepted
25 recording request ("requestId" attribute),

· optionally, the identification of the content to
be recorded ("CRID" attribute),

· optionally, the identification of the user
(<UserId> attribute).

30 The user can also request the deletion of an AV
content that has already been recorded in the network
(<Recorded_Content_Delete> data structure), the deletion
request indicating:

* preferably, the identification of the accepted
35 recording request ("requestId" attribute),

· optionally, the identification of the content to
be recorded ("CRID" attribute),

- optionally, the identification of the user (`<UserId>` attribute).

The steps of the recording method that have just been generally described with reference to Figure 1 will now be described in more detail with reference to Figures 2 to 7.

1. Recording audiovisual content in the network from a network recorder website.

1.1. Discovering a network recorder website.

10 An audiovisual content recorder can make itself known by means of an HTML page on a website.

On clicking on a link indicated on the web page, the user's terminal receives a file of a particular MIME type: "*application/x-TV-Record-Service-Declaration*".

15 This file contains the following information:

- preferably, the address of the recorder on the network (`<RecordServiceAddress>` element),

- preferably, a list of the channels that it can record (`<DeliveryServiceList>` element) containing for each channel:

- * preferably, the address of the channel as defined by the TV Anytime forum ("*serviceURL*" attribute),

- * optionally, the charging policy of the recorder for that channel (`<ChargingPolicy>` element),

- 25 · optionally, the conversion capabilities of the recorder (`<ConversionCapabilities>` element), consisting of:

- * a bit rate reduction capability (`<BitrateConversionCapability>` element),

- 30 * an audiovisual content transcoding capability (`<TranscodingCapability>` element) relating to transcoding a content into different audiovisual coding formats,

- optionally, the protocols supported for transferring the recorded content to the user's terminal
- 35 (e.g. only the FTP mode or another mode is always proposed by default).

In one variant of the invention, the declaration of the network recorder in the network contains the protocols that the network recorder can use to transfer the recorded audiovisual content to the user's terminal.

5 In other words, this enables the user to choose either a direct streaming transfer mode or a downloading mode (off-line relative to recording the content in the network).

10 There follows an example of a file declaring a recorder in the network:

```
<TV_Record_Service_Declaration          xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="TVRecServ.xsd" version="1">
  <RecordServiceAddress>http://www.voila.fr/RecordRequest.rr</RecordServiceAddress>
15  <ConversionCapabilities>
    <BitrateConversionCapability>true</BitrateConversionCapability>
    <TranscodingCapability>MPEG-1</TranscodingCapability>
    <TranscodingCapability>MPEG-4</TranscodingCapability>
  </ConversionCapabilities>
20  <SupportedTransferProtocols>
    <SupportedTransferProtocol value="FTP"/>
    <SupportedTransferProtocol value="HTTP"/>
  </SupportedTransferProtocols>
  <DeliveryServiceList>
25    <DeliveryService serviceURL="dvb://1.2.a">
      <ChargingPolicy xml:lang="en">3 USD for AV contents produced in the last 3 months, 1 USD for
the other contents</ChargingPolicy>
    </DeliveryService>
    <DeliveryService serviceURL="dvb://1.2.b"/>
30    <DeliveryService serviceURL="dvb://1.2.c"/>
  </DeliveryServiceList>
</TV_Record_Service_Declaration>
```

35 This table is used to declare a broadcast audiovisual content recorder to which requests may be submitted at the address indicated by the <RecordServiceAddress> element for content delivery

services or broadcast channels (television channels) indicated by the `<DeliveryServiceURL>` elements.

Accordingly, if the user wishes to record a content broadcast by one of the broadcast channels declared in this way, if the user's terminal does not receive the channel broadcasting the selected content directly or is unable to receive it at the time the content is broadcast, it can request the recording of that content at the address indicated in the `<RecordServiceAddress>` element.

1.2. Requesting by the user of recording in the network.

When a user has discovered in the preceding step that a network recorder is able to record audiovisual content broadcast by a particular broadcast channel and the user wishes to activate a network recorder, the user must send it the request `<TV_Record_Service_Request>`, at the address indicated by the `<RecordServiceAddress>` element of the above table, with the following information:

- preferably, the identification of the user ("`UserId`" attribute),
- optionally, the identification of the protocol to be used to transfer the content after recording,
- optionally, the identification of the coding required for the content to be recorded (which may call for transcoding in the recorder),
- preferably, the identification of the content to be recorded ("`CRID`" attribute),
- optionally, the identification of an instance of that content consisting of:
 - * preferably, the identification of the television channel ("`serviceURL`" attribute),
 - * preferably, the start time ("`start`" attribute),
 - * preferably, the end time ("`end`" attribute) or the duration ("`duration`" attribute),

* optionally, the identity of a particular instance (*"instanceMetadataId"* attribute).

There follows an example of a file requesting recording in the network of two contents using FTP as the recorded content recovery protocol and transcoding to MPEG-4 with a maximum bit rate of 1500 kbps for the "crid://hbc.com/foxes/episode11" content on the television channel "dvb:// 1.4ee2.3f5/" and the "crid://ch1.com/serie/ep12" content on the channel "dvb://1.4ee2.3f4;4f5/" :

```
<TV_Record_Service_Request xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="TVRecServ.xsd" userId="X3YZFdeGH49">
  <RequestedTransferProtocol>FTP</RequestedTransferProtocol>
  <Transcoding>MPEG-4</Transcoding>
  <MaxBitRate>1500</MaxBitRate>
  <ContentIdentification crid="crid://hbc.com/foxes/episode11" serviceURL="dvb:// 1.4ee2.3f5/" start="2001-
04-07T19:00:00.00+01:00" duration="PT1H30M"/>
  <ContentIdentification crid="crid://ch1.com/serie/ep12" serviceURL="dvb://1.4ee2.3f4;4f5/" start="2003-06-
27T12:30:00.00+01:00" duration="PT0H30M" instanceMetadataId="imi:broadcast/1"/>
</TV_Record_Service_Request>
```

Each content to be recorded is identified by its *CRID*, the *serviceURL* that will deliver the content, its start time and its duration (or its end time), and where applicable its instance identification.

The response *<TV_Record_Service_Request_Response>* received in return indicates for each content whose recording has been requested:

- either the success of the recording request (*<RecordRequestSuccess>* element) (Figure 2), giving:
 - * preferably, the identification of the accepted recording request (*"requestId"* attribute),
 - * preferably, the identification of the requested content (*"CRID"* attribute), if a plurality of contents was requested in the same request,

* optionally, the identification of the requested content ("CRID" attribute), if a single content was requested,

5 * optionally, the programmed end of recording time ("recordEndTime" attribute),

* optionally, the time to keep the recorded content ("keepDuration" attribute),

* optionally, the recording cost ("recordCost" and "currency" attributes),

10 * or the failure of the recording request (<RecordRequestFailure> element) (Figure 3), giving:

* preferably, the identification of the content for which the request has failed ("CRID" attribute), if a plurality of contents was requested in the same request,

15 * optionally, the identification of the requested content ("CRID" attribute), if a single content was requested,

* optionally, the reason for failure of the request ("KOREASON" attribute).

20 There follows an example of a response to a recording request with success for two contents (the time to keep and the cost to be paid the being indicated for the second one) and failure for two others:

25 <TV_Record_Service_Request_Response xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xsi:noNamespaceSchemaLocation="TVRecServ.xsd">
 <RecordRequestSuccess crid="crid://hbc.com/foxes/episode11" requestId="12456XD34" recordEndTime="2003-04-07T20:30:00.00+01:00"/>
 <RecordRequestSuccess crid="crid://zzz.com/movie/title1" requestId="156WQ77" recordEndTime="2003-04-
 30 07T20:30:00.00+01:00" keepDuration="PT24H" recordCost="2" currency="USD"/>
 <RecordRequestFailure crid="crid://ch1.com/serie/ep12" KOREASON="unknownCRID"/>
 <RecordRequestFailure crid="crid://chaine5.com/film15" KOREASON="unavailableServiceURL"/>
 </TV_Record_Service_Request_Response>

35 1.3. Management of a request for recording in the network.

After accepting a request for recording in the network, the network recorder is able to monitor changes in the scheduling of the broadcasting of AV contents and to reprogram the recording of the requested contents accordingly.

After a request for recording in the network is accepted, the user has a number of options:

- to cancel the recording request (if the cost is too high or the user changes his or her mind),
- to track the status of a recording request (to find out if the content has been reprogrammed at another date or time, or if the recording is finished).

To cancel a recording request, the user must send a recording request cancellation request (<TV_Record_Request_Cancel> data structure) (Figure 5) containing:

- preferably, the identification of the accepted recording request ("requestId" attribute),
- optionally, the identification of the content to be recorded ("CRID" attribute),
- optionally, the identification of the user (<UserId> attribute).

There follows an example of a recording request cancellation request:

```
<TV_Record_Request_Cancel xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="TVRecServ.xsd" crid="crid://hbc.com/foxes/episode11"
requestId="12456XD34"/>
```

No response is expected from the recorder.

To track the status of a recording request, the user must send a recording request status request (<TV_Record_Request_Status_Request> data structure) (Figure 2) containing:

- preferably, the identification of the accepted recording request ("requestId" attribute),

- optionally, the identification of the content to be recorded ("CRID" attribute),
- optionally, the identification of the user (<UserId> attribute).

5 There follows an example of a "recording status request" request:

```
10        <TV_Record_Request_Status_Request xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
      xsi:noNamespaceSchemaLocation="TVRecServ.xsd" crid="crid://hbc.com/foxes/episode11"
      requestId="12456XD34"/>
```

Several responses are possible. If the content has not yet been recorded (Figure 4), the response from the recorder includes:

- 15 · preferably, the identification of the accepted recording request ("requestId" attribute),
- preferably, the status of the request ("status" attribute, "runningRequest" value),
- optionally, the identification of the content to be recorded ("CRID" attribute),
- 20 · optionally, the programmed end date and time ("callAfter" attribute).

There follows an example of a "content not yet recorded" response:

```
25        <TV_Record_Request_Status_Response xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
      xsi:noNamespaceSchemaLocation="TVRecServ.xsd" crid="crid://hbc.com/foxes/episode11"
      requestId="12456XD34" status="runningRequest" = "2003-06-27T14:30:00.00+01:00"/>
```

30 The "callAfter" attribute enables the terminal to program a timer for repeating a recording status request if there is any chance of obtaining a different response. This is the case if the broadcast time of a content has changed.

35 If the request is not recognized as valid (Figure 7), the response from the recorder includes:

- preferably, the identification of the accepted recording request ("requestId" attribute),
- preferably, the status of the request ("status" attribute, "unknownRequest" value),
- 5 · optionally, the identification of the content to be recorded ("CRID" attribute).

There follows an example of an "unknown recording request" response:

```
10 <TV_Record_Request_Status_Response xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="TVRecServ.xsd" crid="crid://hbc.com/foxes/episode11"
requestId="12456XD34" status="unknownRequest"/>
```

15 This situation can arise if the user's terminal interrogates the network recorder after the end date for keeping a recorded content.

If the request has failed (Figure 6), the recorder responds with:

- preferably, the identification of the accepted recording request ("requestId" attribute),
- 20 · preferably, the status of the request ("status" attribute, "failedRequest" value),
- optionally, the identification of the content to be recorded ("CRID" attribute).

25 There follows an example of a "failed recording request" response:

```
30 <TV_Record_Request_Status_Response xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="TVRecServ.xsd" crid="crid://hbc.com/foxes/episode11"
requestId="12456XD34" status="failedRequest"/>
```

If recording has finished and the content is available, the response from the recorder includes:

- preferably, the identification of the accepted recording request ("requestId" attribute),
- 35 · preferably, the status of the request ("status" attribute, "contentAvailable" value),

- optionally, the identification of the content to be recorded ("*CRID*" attribute),
- optionally, the time to keep the recorded content in the recorder ("*keepDuration*" attribute),
- 5 · preferably, the means of recovering the recorded content ("*contentURL*" attribute).

There follows an example of a "recorded content available in the recorder" response:

```
10 <TV_Record_Request_Status_Response xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="TVRecServ.xsd" crid="crid://hbc.com/foxes/episode11"
requestId="12456XD34" status="contentAvailable"
contentURL="ftp://login:password@ftp.tvrs.fr/user1/av12.mpg"/>
```

15 1.4 Transferring and deleting a content recorded in the network.

If the recorder responds to a content recording request status request by indicating that the content is available, the user's terminal can then download the
20 content, the address of the content being indicated by the *<contentURL>* attribute of the response from the recorder.

The recording will be deleted automatically after a certain time or in response to a specific request from
25 the terminal containing:

- preferably, the identification of the accepted recording request ("*requestId*" attribute),
- optionally, the identification of the content to be recorded ("*CRID*" attribute),
- 30 · optionally, the identification of the user (*<UserId>* attribute).

There follows an example of a request to delete a recording:

```
35 <Recorded_Content_Delete xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="TVRecServ.xsd" crid="crid://hbc.com/foxes/episode11"
requestId="12456XD34"/>
```

No response is expected from the recorder.

2. Recording of an audiovisual content by a network recorder using UDDI and SOAP.

5 2.1 Declaring the network recorder using UDDI (web service).

The technology of web services and in particular of UDDI (Universal Description, Discovery and Integration) services enables recorders of audiovisual content
10 broadcast in the network by broadcast channels to be entered into a directory: the UDDI directory.

The SOAP (Simple Object Access Protocol) technology is used to exchange XML-type data structures.

It must be possible to record in the UDDI directory:
15 · a new service category (or heading): the service for recording audiovisual content in the network with its access point and the operations accepted from users' terminals,

 · a search criterion: the identifier of each
20 broadcast channel (television channel).

Thus a user terminal looking for a network recorder can consult the directory, supplying one or more broadcast channel (television channel) identifiers and requesting in return a means of addressing directly
25 recorders that satisfy the search criteria.

The new search criterion in the UDDI directory that consists of the television channel identifier, for example, must be the subject of the definition of a new UDDI tModel, here called "*serviceURL*" (in conformance
30 with section 1.6.4 of the UDDI specifications relating to the definition of "tModel"), to declare the audiovisual content broadcast channels. It is given the name "*tv-record-org:serviceURL*". This is an authority that must request the recording of this new "tModel". The entity
35 "*tv-record-org*" is any entity, for example "*tv-anytime-org*". This leads to declaring a key with the same name "*uddi:tv-record.org:serviceURL*".

The declaration of that key also includes references to the specifications of this "tModel" by the organization requesting its insertion

"<overviewDoc><overviewURL>" and the "<categoryBag>"
 5 element contains standard information included in any "tModel" declaration.

```

<tModel tModelKey="uddi:tv-record.org:serviceURL">
  <name>tv-record-org:serviceURL</name>
  10 <description xml:lang="en">Category system for each delivery service handled by a recording
  service</description>
  <overviewDoc>
    <overviewURL useType="text">
      ftp://pub:pub@ftp.francetelecom.fr/pub/Spec/Record_tModel.zip
  15 </overviewURL>
    </overviewDoc>
    <categoryBag>
      <keyedReference keyName="uddi-org:types:categorization"
keyValue="categorization" tModelKey="uddi:uddi.org:categorization:types"/>
  20 <keyedReference keyName="uddi-org:types:unchecked"
keyValue="unchecked" tModelKey="uddi:uddi.org:categorization:types"/>
    </categoryBag>
  </tModel>

```

25 It is also necessary to define a "tModel port" for sending requests to the audiovisual content recorder as follows: this "tModel" describes the service for transferring "submit_Data" requests to the content recorder in the network, the use of which will be
 30 illustrated later:

```

<tModel tModelKey="uddi:tv-record.org:submit_Data_v10">
  <name>tv-record-org:submit_Data_v10</name>
  <description xml:lang="en">TV Record WSDL interface for submit_Data port</description>
  35 <overviewDoc>
    <overviewURL useType="wsdlInterface">
      http://www.tv-record.org/wsdl/tvr_transport_v10.wsdl#submit_Data_SOAP

```

```

    </overviewURL>
    </overviewDoc>
    <overviewDoc>
      <overviewURL useType="text">
5      ftp://tvr:tvr@ftp.voila.fr/spec/tvr_xxV10.zip
      </overviewURL>
    </overviewDoc>
    <categoryBag>
      <keyedReference keyName="uddi-org:types:wsdl" keyValue="wsdlSpec"
10      tModelKey="uddi:uddi.org:categorization:types"/>
      <keyedReference keyName="uddi-org:types:soap" keyValue="soapSpec"
      tModelKey="uddi:uddi.org:categorization:types"/>
      <keyedReference keyName="uddi-org:types:xml" keyValue="xmlSpec"
      tModelKey="uddi:uddi.org:categorization:types"/>
15      <keyedReference keyName="uddi-org:types:specification"
      keyValue="specification" tModelKey="uddi:uddi.org:categorization:types"/>
    </categoryBag>
  </tModel>

```

20 To make itself known, a broadcast audiovisual content recorder must declare its recording capabilities using the *"save_binding"* method (see the UDDI API publication), assuming that the appropriate parental structures *"businessEntity"* and *"businessService"* have

25 already been declared, referring to the "tModel" defined previously:

```

<save_binding xmlns="urn:uddi-org:api_v3">
  <bindingTemplate>
30    <description xml:lang="fr">Declaration of an audiovisual content recording service for one or more
    television channels </description>
    <accessPoint useType="endPoint">
      http://www.voila.fr/movies
    </accessPoint>
35    <tModelInstanceDetails>
      <tModelInstanceInfo tModelKey="uddi:tv-record.org:submit_Data_v10">
        <instanceDetails>

```

```

    <instanceParms><![CDATA[
        <?xml version="1.0" encoding="utf-8"?>
        <describe_submit_Data_Result serviceVersion="3"
            xmlns="http://www.tv-anytime.org/2002/11/transport">
5    <ConversionCapabilities>
        <BitrateConversionCapability>true</BitrateConversionCapability>
        <TranscodingCapability>MPEG-1</TranscodingCapability>
        <TranscodingCapability>MPEG-4</TranscodingCapability>
        </ConversionCapabilities>
10    <SupportedTransferProtocols>
        <SupportedTransferProtocol value="FTP"/>
        <SupportedTransferProtocol value="HTTP"/>
        </SupportedTransferProtocols>
        <DeliveryServiceList>
15    <DeliveryService serviceURL="dvb://1.2.a">
        <ChargingPolicy xml:lang="en">3 USD for AV contents produced in the last 3 months, 1 USD for the other
contents</ChargingPolicy>
        </DeliveryService>
        <DeliveryService serviceURL="dvb://1.2.b"/>
20    <DeliveryService serviceURL="dvb://1.2.c"/>
        </DeliveryServiceList>
        </describe_submit_Data_Result>
    ]]></instanceParms>
    </instanceDetails>
25    </tModelInstanceInfo>
    </tModelInstanceDetails>
    <categoryBag>
        <keyedReference tModelKey="uddi:tv-record.org:serviceURL"
            keyValue="dvb://1.2.a"/>
30    <keyedReference tModelKey="uddi:tv-record.org:serviceURL"
            keyValue="dvb://1.2.b"/>
        <keyedReference tModelKey="uddi:tv-record.org:serviceURL"
            keyValue="dvb://1.2.c"/>
        </categoryBag>
35    </bindingTemplate>
</save_binding>

```

The `<accessPoint>` element provides the HTTP address of the recorder to which the "submit_Data" request must be sent.

5 The `<instanceParms>` element contains the declaration of what may be expected of the recorder (content of the data structure `<TV_Record_Service_Declaration>` defined for the first embodiment) which defines the transcoding, bit rate production and transfer protocol capabilities, the list of recordable broadcast channels and the
10 charging policy.

The `<categoryBag>` element contains a list of the broadcast channels that the recorder is able to record.

2.2 Discovering a network recorder using a web service.

15 The technology of web services and of UDDI (Universal Description, Discovery and Integration) services in particular also offers terminals the option, if they have an Internet connection, of discovering broadcast audiovisual content recorders by consulting the
20 directory, without necessitating any prior knowledge.

Thus any terminal can use a node of the UDDI business directory (which has well known addresses) to find broadcast individual content recorders using the `<find_binding>` command as shown below:

25
`<find_binding xmlns="urn:uddi-org:api_v3">`
`<tModelBag>`
`<tModelKey>uddi:tv-record.org:submit_Data_v10</tModelKey>`
`</tModelBag>`
30 `<categoryBag>`
`<keyedReference tModelKey="uddi:tv-record.org:serviceURL"`
`keyValue="dvb://1.2.a"/>`
`<keyedReference tModelKey="uddi:tv-record.org:serviceURL"`
`keyValue="dvb://1.2.c"/>`
35 `</categoryBag>`
`</find_binding>`

In this example, the terminal is looking for a network recorder for the channels or television channels "dvb://1.2.a" and "dvb://1.2.c".

In response, the terminal receives a
 5 <bindingTemplate> list that matches its request (recorded in the directory of services by the command <save_binding>).

2.3 Requesting recording in the network

After choosing an audiovisual content recorder, the
 10 terminal can send the following request using the SOAP (Simple Object Access Protocol) to request the recording of a content (the request encapsulating the <TV_Record_Service_Request> request defined in the preceding embodiment):

15

```
POST /tvr/md-service HTTP/1.0
```

```
Host: www.voila.fr
```

```
Content-Type: text/xml; charset="utf-8"
```

```
Content-Length: nnnn
```

20

```
Accept-Encoding: deflate
```

```
SOAPAction: "submit_Data"
```

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<Envelope xmlns="http://schemas.xmlsoap.org/soap/envelope/">
```

25

```
<Body>
```

```
<submit_Data xmlns="http://www.tv-record.org/2002/11/transport">
```

```
<TV_Record_Service_Request
```

```
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
```

```
  xsi:noNamespaceSchemaLocation="TVRecServ.xsd" userId="XcGHJ63DX">
```

30

```
<RequestedTransferProtocol>FTP</RequestedTransferProtocol>
```

```
<Transcoding>MPEG-4</Transcoding>
```

```
<MaxBitRate>1500</MaxBitRate>
```

```
<ContentIdentification crid="crid://hbc.com/foxes/episode11"
```

```
  serviceURL="dvb:// 1.4ee2.3f5/"
```

35

```
  start="2001-04-07T19:00:00.00+01:00" duration="PT1H30M"/>
```

```
<ContentIdentification crid="crid://ch1.com/serie/ep12"
```

```
  serviceURL="dvb://1.4ee2.3f4;4f5/"
```

```
        start="2003-06-27T12:30:00.00+01:00" duration="PT0H30M"
        instanceMetadataId="imi:broadcast/1"/>
    </TV_Record_Service_Request>
</submit_Data>
5  </Body>
</Envelope>
```

10 In return the terminal receives the following
response for recording requests that have succeeded and
other recording requests that have failed:

```
HTTP/1.1 200 OK
Content-Type: text/xml; charset="utf-8"
Content-Length: nnnn
15 Content-Encoding: deflate

<?xml version="1.0" encoding="UTF-8"?>
<Envelope xmlns="http://www.w3.org/2002/06/soap-envelope">
    <Body>
20    <submit_Data_Result xmlns=" http://schemas.xmlsoap.org/soap/envelope/">
        <TV_Record_Service_Request_Response
            xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
            xsi:noNamespaceSchemaLocation="TVRecServ.xsd">
            <RecordRequestSuccess crid="crid://hbc.com/foxes/episode11"
25            requestId="12456XD34"
            recordEndTime="2003-04-07T20:30:00.00+01:00"/>
            <RecordRequestSuccess crid="crid://zzz.com/movie/title1"
            requestId="156WQ77"
            recordEndTime="2003-04-07T20:30:00.00+01:00"
30            keepDuration="PT24H" recordCost="2" currency="USD"/>
            <RecordRequestFailure crid="crid://ch1.com/serie/ep12"
            KOreason="unknownCRID"/>
            <RecordRequestFailure crid="crid://chaine5.com/film15"
            KOreason="unavailableServiceURL"/>
35    </TV_Record_Service_Request_Response>
    </submit_Data_Result>
</Body>
```


</Envelope>

The same procedure is used to encapsulate other
requests defined in the preceding embodiment for other
5 steps of recording audiovisual content in the network.